


END VIEW

PROVIDED EQUIPMENT

- 1. 16"ø PIPE STUB W/ 2" NPT FOR VENT (OVERFLOW SKIMMER)
 2. 2"ø FTG. FOR VENT
 3. VELOCITY HEAD DIFFUSION BAFFLE

- 3. VELOCITY HEAD DIFFUSION BAFFLE
 4. WEAR PLATE
 5. 16"ø PIPE STUB (INLET)
 6. UNDERFLOW BAFFLE
 7. 2"ø FULL CPLG. FOR PUMP MOUNTING
 8. STRIKER PLATES
 9. 4"ø FTG. FOR GAUGE WITH PLUG
 10. 24"ø MANWAY

- 11. 2"Ø FTG. FOR CONDUIT
 12. 2"Ø FTG. W/ MOUNT FOR LEVEL SENSOR
 13. LIFTING LUG
- 14. GROUNDING LUG 15. HIGHLAND STANDARD INTERNAL LADDER 16. 4"Ø FTG. FOR VENT



ELEVATION

GENERAL SPECIFICATIONS

NO. REQ'D: (1)
CAPACITY: 60,000 GALLON
TYPE: SINGLE WALL, ABOVEGROUND
MATERIAL: MILD CARBON STEEL GAUGE: SHELL- 3/8" HEADS- 3/8"

SURFACE PREP:

SSPC-SP 6 BLAST EXTERIOR SSPC-SP 10 BLAST INTERIOR

COATING: MATERIAL / THICKNESS

WHITE URETHANE (3-5 MILS)

INTERIOR-

HighDRO®-LINER PLUS POLYURETHANE (15 MILS) CONSTRUCTION : LAP FIT & WELD ALL EXTERIOR SEAMS

OPERATING PRESSURE: ATMOSPHERIC ALL VENT PIPING BY INSTALLER

LIFTING LUGS PLACED AS NEEDED PER FAB SHOP

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING OR ANY PART THEREOF MUST
NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION
OF HIGHLAND TANK.
HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED
ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER
IS RESPONSIBLE FOR VERIFYING CORRECTHESS OF SIZE / LOCATION
OF FITTINGS, ACCESSORIES & COATINGS SHOWN ON THIS DRAWING

