
Built on Tradition





LevelShield

HT-6100

Liquid Inventory Management

Level Shield is a cutting edge, easy to install technology for fixed and mobile tanks that allows total control of the management of liquid products and inventories. High-LINK[®] combines data and smart alerts to allow users to efficiently manage their liquid inventory via a single platform cloud-based software application.

Level Shield has a variety of level sensing hardware options that work seamlessly with our High-LINK[®] software platform to eliminate any human intervention to determine tank levels.

High-LINK[®] Integrated Systems couple superior steel tank products with state-of-the-art electronic management devices and SCI's proprietary software providing real-time data to optimize usage and transfer of any liquid operation.

Level Shield Benefits


- · Manage liquid levels from anywhere
- Save money and increase efficiency in inventory management and capacity
- Analyze data in real time
- Optimize operations with effective level management
- · Continuous water detection in tanks
- Verify physical delivery and real-time comparison with purchase orders and the bill of lading from vendors
- Analysis of gallons treated, stored, processed and bypassed
- Fully customizable and remotely programmed alerts include: liquid level, overfill, volume pumped, etc
- · Auto-generated reports based on user-defined intervals

Refer to HT-6114 Series-G for vertical tank applications and HT-6117 Series-P for horizontal tank applications



LevelShield Specifications

Wired Probe



High-LINK[®] Integrated Systems operate on web-based Microsoft operating system computer platforms providing critical data via any mobile device.

Each High-LINK® Integrated System is customized for site-specific conditions and requirements. Our management tools are user-friendly and can be managed remotely.

Utilizing big data analytics improves the business decision making process, elevating efficiency, reducing operating costs and system optimization.

High-LINK[®] Integrated Systems have been engineered to work seamlessly with all of our storage tanks and process vessels with each system being tailored to your needs.

Level Shield Specifications

- 2-Floats for level monitoring product & water
- Measuring accuracy up to ± 0.02"
- Integrated sensor for temperature-compensated volume monitoring
- RS-485 Wired Communication Standard
- Measuring range along the complete probe length
- Standard lengths of 60" to 167" (Longer probe lengths are available upon request)
- Resolution ± .004"
- Operating temperature: minus 40° to 185°F

Physical

- Floats: SP-P for product, SP-A for water
- Stem: 316L stainless steel tubing
- Tank connection: 2" NPT

Certifications

- Explosion-proof ATEX CESI & IENRIS-OIML R85 (pending)
- Class 1 Division 1&2 (Safer Barrier)
- Class 1 Zone 1&2 (Safer Barrier)

Specifications for magnetostrictive probes only. Other level-sensing equipment is available upon request.

High-LINK[®] Provides peace of mind 24/7



Stoystown, PA One Highland Rd. (814) 893-5701

Manheim, PA 4535 Elizabethtown Rd. 958 19th St. Stoystown, PA 15563 Manheim, PA 17545 (717) 664-0600

Watervliet, NY Watervliet, NY 12189 (518) 273-0801

Greensboro, NC 2700 Patterson St. Greensboro, NC 27407 (336) 218-0801

Friedens, PA 1510 Stoystown Rd. 4701 White Lake Rd. 9517 Lake St. Friedens, PA 15541 (814) 443-6800

Clarkston, MI (248) 625-8700

Mancelona, MI Clarkston, MI 48346 Mancelona, MI 49659 (231) 587-8412

MADE IN