



Underground Cylindrical Oil/Water Separator Installation Start-up Checklist

This form is intended to document all of the important information regarding the installation and start-up of your Highland Tank Oil/Water Separator (OWS).

For accuracy, to ensure proper installation, and keep any warranty in force, this important document should be completed at the time of start-up. A copy of this document should be maintained at the OWS installation site, maintenance office and owner's office.

Person Conducting Start-up:

Print name: _____ Title: _____

Signature: _____ Date: _____

Installation Acceptance (see last page for any installation comments)

Customer

Print name: _____ Title: _____

Signature: _____ Date: _____

Installer

Print name: _____ Title: _____

Signature: _____ Date: _____

Highland Tank
One Highland Road
Stoystown, PA 15563
www.highlandtank.com
wastewater@highlandtank.com

Underground Cylindrical Oil/Water Separator Installation Start-up Checklist

General Operating Notes

Periodic maintenance is required to remove sand, trash, sludge and oil from the coalescers and the unit as a whole. For units processing any rainwater, an inspection after a heavy rainfall event is recommended.


It is recommended that the OWS be cleaned at least once a year. Annual cleaning consists of removing the oil buildup on the surfaces of the OWS walls and coalescer plates with steam or high-pressure water. Prior to performing any maintenance, stop all flow to the OWS. Then, using suction, remove all fluid and solids from the OWS and dispose of properly.

Perform maintenance according to Highland Tank Underground Rectangular User's Manual available at www.highlandtank.com/AdminHighlandData/FileDataAdditional/resource_106.pdf. Since OWS designs will vary with sites, it is essential to adhere strictly to the manufacturer's instructions for cleaning and maintenance.

If contaminants are present, or if detergents are used in the cleaning process, always be sure to pump out before reactivating the system and reopening the valve on the influent line.

Factors that adversely affect OWS performance

- Excessive turbulence
- Excessive influent flow rate
- Excessive oil storage
- Pumping into the OWS
- Detergents or surfactants
- Excessive sludge build-up



IMPORTANT: OWS is to be filled with clean/fresh water prior to being put into service.



Highland Tank®

Unmatched Quality & Service Since 1946

www.highlandtank.com
One Highland Road
Stoystown, PA 15563
PH: 814-893-5701

Underground Cylindrical Oil/Water Separator Start-up Report

PLEASE PRINT

Owner of OWS: _____ Installation Date: _____

Location of OWS: _____

Model / Size: _____ Start-up Date: _____

Sold to

Customer: _____

Address: _____

City: _____ State: ____ Zip: _____

Phone: (____) _____

Contact: _____

Start-up Attendees (Please print)

Installation Site

Customer: _____

Address: _____

City: _____ State: ____ Zip: _____

Phone: (____) _____

Contact: _____

Installing Company

Company Name: _____

Installer Contact: _____

Phone: (____) _____

Highland Representative

Name: _____

Phone: (____) _____

Email: _____

IMPORTANT: OWS is to be filled with clean/fresh water prior to being put into service.



Unmatched Quality & Service Since 1946

www.highlandtank.com
One Highland Road
Stoystown, PA 15563
PH: 814-893-5701

Underground Cylindrical Oil/Water Separator Start-up Report

OWS Specifications:

Model: - _____ Highland Work Order #: _____
Set up for _____ GPM flow rate Serial Number: (HighGuard) _____
Construction: SW or DW (circle one) Serial Number: (UL) _____
Inlet size: _____ Outlet size: _____ Serial Number (other): _____
Manways:
#1 Diameter _____", Extension Height _____", #2 Diameter _____", Extension Height _____",
#3 Diameter _____", Extension Height _____", #4 Diameter _____", Extension Height _____",
Exterior Coating: Interior Lining: _____ None
_____ HighGuard Polyurethane _____ Polyurethane
_____ ACT-100U or STI-P3 Polyurethane (circle one) _____ Epoxy Other _____

Installation Questionnaire

Circle One

Have the OWS and all accessories been checked to verify that all items and correct items were received?

Yes No
N/A

Has the OWS been installed in accordance with the Highland Tank HighGuard (or other) installation instructions and Highland Tank Underground Cylindrical Oil/Water OWS User's Manual?

Yes No
N/A

Available at www.highlandtank.com/AdminHighlandData/FileDataAdditional/resource_106.pdf

Has the HighGuard (or other) protection system installation checklist been completed in full?

Yes No
N/A

Has the OWS been installed level in accordance with installation instruction specifications?

Yes No

Has the OWS been installed with a separate atmospheric vent from the inlet pipe in accordance with applicable code requirements? (Not applicable on systems with Pumped influent)

Yes No
N/A

Has the OWS been installed with a separate atmospheric vent from the outlet pipe in accordance with applicable code requirements? (Not applicable on systems with Pumped effluent)

Yes No
N/A

Has the OWS been installed with separate atmospheric vents from the OWS body in accordance with applicable code requirements?

Yes No

Have all accessories been received and installed by the installer?

Yes No
N/A

Has the OWS been filled with clean/fresh water prior to being put into service?

Yes No
N/A

Has the operation of the OWS detailed in the Highland Tank Underground Cylindrical OWS User's Manual been explained to appropriate personnel?

Yes No
N/A

Stoystown, PA / Manheim, PA / Watervliet, NY / Lebanon, PA / Greensboro, NC / Friedens, PA / Clarkston, MI / Mancelona, MI



Available at www.highlandtank.com/AdminHighlandData/FileDataAdditional/resource_106.pdf

Has the need for periodic maintenance and the recommended procedure for this maintenance been explained to the appropriate personnel?

Yes No
N/A

IMPORTANT: OWS is to be filled with clean/fresh water prior to being put into service.

Underground Cylindrical Oil/Water Separator Start-up Report

OWS Installation Information

Backfill material used: _____

Hold-Down Pad or Deadmen (circle one):

Yes No
N/A

Hold-Down Straps with Liners:

Yes No
N/A

Oil Skimmer

Is the OWS equipped with an oil-skimming device?

Yes No

Skimmer Type: _____ Model # _____

Has skimmer been installed in accordance with manufacturer's instructions? Has it been tested

Yes No
N/A

and is it working properly?

If "No", have you explained to the operator how to adjust the skimmer?

Yes No
N/A

Sensor(s) and Alarm/Control Panel

Is OWS equipped with an Alarm/Control Panel and Sensor(s)?

Yes No

Alarm/Control Panel Model: _____ Incoming Voltage: _____ VAC, _____ Phase

Has the Alarm/Control Panel been installed in accordance with manufacturer's instructions?

Has it been tested and is it working properly?

Yes No
N/A

Has the Oil Interface Level Sensor been installed in accordance with manufacturer's instructions?

Has it been tested and is it working properly?

Yes No
N/A

Has the High Fluid Level Sensor been installed in accordance with manufacturer's instructions?

Has it been tested and is it working properly?

Yes No
N/A



Pumps

Is OWS equipped with an influent pump system? Yes No

Pump: Make - Model – Type: _____

Is pump mounting and piping configuration correct based on the manufacturer's specifications? Yes No

Is OWS equipped with an effluent pump system? Yes No

Pump: Make - Model – Type: _____

Has the operation of the Alarm Panel, sensor(s) and pump system been fully explained to the appropriate personnel? Yes No

IMPORTANT: OWS is to be filled with clean/fresh water prior to being put into service.

Underground Cylindrical Oil/Water Separator Start-up Report

Application

How is this OWS going to be used? _____

What type of Hydrocarbon is to be separated? _____

Specific Gravity(s): _____

Are there any detergents or solvents being used that will flow into the OWS? Yes No
N/A

If yes, what are they? _____

Have the effects of detergents/solvents been explained? Yes No
N/A

Where will this unit be discharging? _____

Have the effects of an emulsifying influent pump been explained? Yes No
N/A



Maintenance

Does the customer have a copy of Highland Tank Underground Cylindrical OWS User's Manual?

Yes No
N/A

Have the installation, operation and maintenance instructions been discussed with the customer?

Yes No
N/A

IMPORTANT: OWS is to be filled with clean/fresh water prior to being put into service.

Underground Cylindrical Oil/Water Separator Start-up Report

Differences noted (Missing or incorrect items): _____

Follow-up required: _____

Corrective action: _____



Highland Tank®

Unmatched Quality & Service Since 1946

www.highlandtank.com
One Highland Road
Stoystown, PA 15563
PH: 814-893-5701

Start-up date: ____ / ____ / ____ By: _____

Notes: _____

Local Highland Representative: _____ Phone: () - _____

Email: _____