



accessories & options

polyester hold-down straps

HT-1091

PRODUCT DETAILS

Polyester Hold-down Straps are designed to help secure tanks underground in areas having ground water. Strap liners are not needed - when installed correctly, there are not any metallic components in the strap system that can make contact with the tank.

Hold-down Straps are made from 100% polyester webbing.

Highland's Polyester Straps are fabricated with a large reinforced loop at each end for securing the underground cylindrical storage vessel.

Included with each strap is a length of 1/2" diameter wire rope and three cable clamps for attaching the strap to one side of the concrete anchoring system.


A turnbuckle is used for attaching the strap to the anchoring on the other side of the tank.

These straps are designed for and must be used in a system that has adequately sized concrete anchoring to counteract the tank's natural buoyant forces. Polyester Straps are intended for underground use ONLY.


INSTALLATION INSTRUCTIONS

- Open turnbuckle completely.
- Lay polyester strap over tank.
- Attach one end of turnbuckle to loop of polyester strap.
- Attach the other end of turnbuckle through tie-down anchor in deadman anchor or hold-down pad (by contractor) on one side of tank.
- Go to opposite side of tank.
- Wrap 1/2" wire rope attached to the other end of the polyester strap through the tie-down anchor in deadman anchor or hold-down pad (by contractor).
- Pull rope tight. Insert thimble at wire rope and tie-down juncture.
- Secure wire rope with (3) supplied cable clamps.
- Go back to turnbuckle side of vessel.
- Tighten turnbuckle to secure tank.
- After taking up slack in the polyester strap, tighten turnbuckle to remove any slack/stretch in strap.
- Recheck strap tightness and adjust just as needed prior to backfilling.

Polyester Hold-down Strap Sizing & Installation Guide



Typical Deadman Installation




Tank Diameter	Turn-Buckle Diameter	Strap Length
3'2"	3/4"	73"
4'0"	3/4"	89"
5'4"	1-1/4"	124"
6'0"	1-1/4"	137"
7'0"	1-1/4"	172"
8'0"	1-1/4"	194"
10'0"	1-1/4"	242"
10'6"	1-1/4"	242"

Polyester Hold-Down Straps for tanks larger than 10'6" diameter are NOT available. Please contact Highland for information about our Steel Hold-Down Straps.

*strong, safe
& easy to
install*

Typical Hold-down Pad Installation



Note: * Contractor Supplied Items



Stoystown, PA
One Highland Road
Stoystown, PA 15563-0338
814.893.5701

Manheim, PA
4535 Elizabethtown Road
Manheim, PA 17545-9410
717.664.0600

Watervliet, NY
958 19th Street
Watervliet, NY 12189-1752
518.273.0801

Greensboro, NC
2700 Patterson Street
Greensboro, NC 27407-2317
336.218.0801

Lebanon, PA
2225 Chestnut Street
Lebanon, PA 17042-2504
717.664.0602

Friedens, PA
1510 Stoystown Road
Friedens, PA 15541-7402
814.443.6800

Clarkston, MI
4701 White Lake Road
Clarkston, MI 48346-2554
248.625.8700

Mancelona, MI
9517 Lake Street
Mancelona, MI 49659-7968
231.587.8412



PROUDLY MADE IN AMERICA